



Undervoltage release, 230 V, non-delayed, 1HP

Part no. Z-USA/230
Catalog No. 248289
Alternate Catalog No. Z-USA/230
EL-Nummer (Norway) 0001609472

Delivery program

Basic function			Accessories for miniature circuit-breaker
Basic function accessories			Undervoltage release
Application			Switchgear for industrial and advanced commercial applications
Tripping		s...	non-delayed
Product range			Accessory
Side mounting			for fitting on left to: FAZ
Contact sequence			

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecI@ss10.0.1-27-14-35-02 [AKE327013])			
Device fitting			Universal
Additional equipment			Under voltage coil
Attached at delivery			No
Assembly width (TE)			1
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	230
Voltage type for actuating			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			1
Suitable for max. current main contact unit		A	0

Dimensions

