



Auxiliary contact, 1N/O+1N/C

Part no. Z-SC
Catalog No. 248862
EL-Nummer (Norway) 4355534

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	0
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	0
Static heat dissipation, non-current-dependent	P_{vs}	W	0.5
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature max.		°C	-40
Operating ambient temperature max.		°C	60
			0

Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])			
Device fitting			Auxiliary switch / relay
Additional equipment			Auxiliary switch
Attached at delivery			No
Assembly width (TE)			0.5
Number of normally open contacts			1
Number of normally closed contacts			1
Number of change-over contacts			0
Number of fault-signal switches			0
Rated switch current		A	3
Nominal rated voltage		V	230
Control voltage type			AC
With autotest for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			0
Suitable for max. current main contact unit		A	0