


220-240V
50/60 HzIK
08IP
65

Hermetic LED luminaire, water-jet proof, intended for mounting inside industrial or architectural objects.

TECHNICAL DATA

Mounting: directly on the ceiling, with mounting brackets (included), suspended, on chains, on wire suspension (on request)

Body: plastic

Colour: light gray

Diffuser: polycarbonate

ELECTRICAL DATA

Power supply efficiency: >90%

Power: 220-240V 50/60Hz

Includes light source: yes

Type of equipment: STANDARD, STANDARD + through wiring (TW) 5x1,5 mm², STANDARD + single-sided through wiring

Electrical connection: max 3x2,5 mm² wire, max 5x1,5 mm² wire

OPTICAL DATA

Light distribution: omnidirectional

Way of lighting: direct

Type of optic: opal diffuser

GENERAL DATA

Lifetime (L80B10): 60 000 h

Available on request: emergency module 3h, available with connection to a central battery power supply, radar motion detector, twilight sensor

Warranty: 5 years


Application: parking areas, production halls, warehouses, assembly halls, warehouses, electricity plants, mills, workshops, wood and paper industry



5 year warranty

Code	Luminaire power [W]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra	Operating temperature range [°C]
Type of equipment: STANDARD						
090410.5L01.011	34	4450	131	4000	≥80	-25 ... +35
090410.5L02.011	50	6800	136	4000	≥80	-25 ... +35
Type of equipment: STANDARD + through wiring (TW) 5x1,5 mm²						
090410.5L01.011.938	34	4450	131	4000	≥80	-25 ... +35
090410.5L02.011.938	50	6800	136	4000	≥80	-25 ... +35
Type of equipment: STANDARD + single-sided through wiring						
090410.5L01.011.828	34	4450	131	4000	≥80	-25 ... +35
090410.5L02.011.828	50	6800	136	4000	≥80	-25 ... +35

Code	Dimensions [mm] LWH	Mounting dimensions [mm] D	Pallet quantity	Net weight [kg]
Type of equipment: STANDARD				
090410.5L01.011	1245 100 90	766	105	1.7
090410.5L02.011	1245 100 90	766	105	1.7
Type of equipment: STANDARD + through wiring (TW) 5x1,5 mm²				
090410.5L01.011.938	1245 100 90	766	105	1.7
090410.5L02.011.938	1245 100 90	766	105	1.7
Type of equipment: STANDARD + single-sided through wiring				
090410.5L01.011.828	1245 100 90	766	105	1.7
090410.5L02.011.828	1245 100 90	766	105	1.7



The luminaires are not intended for mounting in places exposed to atmospheric conditions, in car washes, in rooms where washing with pressure washers is used, in livestock rooms, in aggressive environments, etc.

Luminous flux tolerance +/- 10%.

Power tolerance +/- 5%.

Up-to-date product info and General Warranty Terms available on our website www.luglightfactory.com

Detailed information on luminous fluxes and powers for individual indexes are indicated on the product data sheet.

The parameters in the data sheet are given for Ta=25°C.

ACCESSORIES


□ 150020.00999

ATLANTYK 2.0 ECO LED choke




150060.00987

Gripper (1 pcs.)

LIGHT BEAM CURVES**WAY OF LIGHTING**

090410.5L01.011



The luminaires are not intended for mounting in places exposed to atmospheric conditions, in car washes, in rooms where washing with pressure washers is used, in livestock rooms, in aggressive environments, etc.

Luminous flux tolerance +/- 10%.

Power tolerance +/- 5%.

Up-to-date product info and General Warranty Terms available on our website www.luglightfactory.com

Detailed information on luminous fluxes and powers for individual indexes are indicated on the product data sheet.

The parameters in the data sheet are given for $T_a=25^{\circ}\text{C}$.