






# DRIVERS LIFUD



Referencia	Potencia Máx.	Voltaje de Entrada	Voltaje de Salida	Corriente de Salida	PF	Temp F	Temp Corte	Dimensión
<b>Serie 0-10V/PWM/Rx Dimable y Ajustable DIP Switch</b>								
  <b>Free Flicker</b>	24W	220-240V	27-40V DC	600mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm
	26W	220-240V	27-40V DC	650mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm
	28W	220-240V	27-40V DC	700mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm
	30W	220-240V	27-40V DC	750mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm
	32W	220-240V	27-40V DC	800mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm
LF-GDE040YP	36W	220-240V	27-42V DC	850mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm
	38W	220-240V	27-42V DC	900mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm
	40W	220-240V	27-42V DC	950mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm
	42W	220-240V	27-42V DC	1000mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm
	44W	220-240V	27-42V DC	1050mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25.4mm



Referencia	Potencia Máx.	Voltaje de Entrada	Voltaje de Salida	Corriente de Salida	PF	Temp F	Temp Corte	Dimensión
<b>Serie DALI &amp; Push Dim &amp; 0-10V/PWM/Rx Dim &amp; DIP Switch</b>								
  <b>Free Flicker</b>	20W	220-240V	46-57V	350mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	23W	220-240V	46-57V	400mA	0.90	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	26W	220-240V	46-57V	450mA	0.90	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	29W	220-240V	46-57V	500mA	0.90	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	31W	220-240V	46-57V	550mA	0.90	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	34W	220-240V	46-57V	600mA	0.90	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	37W	220-240V	46-57V	650mA	0.90	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	40W	220-240V	46-57V	700mA	0.90	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	40W	220-240V	36-53V	750mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	40W	220-240V	36-50V	800mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	40W	220-240V	36-47V	850mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	40W	220-240V	35-45V	900mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
	40W	220-240V	30-42V	950mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm
40W	220-240V	30-40V	1000mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm	
40W	220-240V	30-38V	1050mA	0.95	-30°C - 50°C	-40°C - 80°C	124.5x82.5x25mm	



# DRIVERS LIFUD

Referencia	Potencia Máx.	Voltaje de Entrada	Voltaje de Salida	Corriente de Salida	PF	Temp F	Temp Corte	Dimensión	
<b>Serie AC220-240V</b>									
	LF-GIR015YM	14W	220-240V	25-40V DC	350mA	0.90	-30°C - 50°C	-40°C - 80°C	96x36x24mm
		21W	220-240V	25-42V DC	500mA	0.95	-30°C - 50°C	-40°C - 80°C	135x36x25mm
	LF-GIR030YM	25W	220-240V	25-42V DC	600mA	0.95	-30°C - 50°C	-40°C - 80°C	135x36x25mm
		29W	220-240V	25-42V DC	700mA	0.95	-30°C - 50°C	-40°C - 80°C	135x36x25mm
LF-GIR040YM		38W	220-240V	25-42V DC	900mA	0.96	-30°C - 50°C	-40°C - 80°C	135x36x25mm
		42W	220-240V	25-42V DC	1000mA	0.96	-30°C - 50°C	-40°C - 80°C	135x36x25mm
LF-GIR060YM	59W	220-240V	25-42V DC	1400mA	0.96	-30°C - 50°C	-40°C - 80°C	139.5x43x29.3mm	

Referencia	Potencia Máx.	Voltaje de Entrada	Voltaje de Salida	Corriente de Salida	PF	Temp F	Temp Corte	Dimensión	
<b>Serie AC220-240V</b>									
	LF-GIF015YA	14W	220-240V	25-40V	350mA	0.90	-30°C - 50°C	-40°C - 80°C	96x36x24mm
	LF-GIF022YA	20W	220-240V	25-40V	500mA	0.90	-30°C - 50°C	-40°C - 80°C	115x41x28mm
	LF-GIF030YA(H)	28W	220-240V	33-40V	700mA	0.94	-30°C - 50°C	-40°C - 80°C	115x41x28mm
		38W	220-240V	33-40V	950mA	0.95	-30°C - 50°C	-40°C - 80°C	115x41x28mm
<b>Free Flicker</b>	LF-GIF040YA(H)	40W	220-240V	33-40V	1000mA	0.95	-30°C - 50°C	-40°C - 80°C	115x41x28mm
		42W	220-240V	33-40V	1050mA	0.95	-30°C - 50°C	-40°C - 80°C	115x41x28mm
LF-GIF050YA(L)	40W	220-240V	25-33V	1200mA	0.95	-30°C - 50°C	-40°C - 80°C	139x43x29mm	
LF-GIF060YA(H)	62W	220-240V	33-40V	1550mA	0.95	-30°C - 50°C	-40°C - 80°C	139x43x29mm	

Referencia	Potencia Máx.	Voltaje de Entrada	Voltaje de Salida	Corriente de Salida	PF	Temp F	Temp Corte	Dimensión	
<b>Serie 24V IP20</b>									
	LF-GMR030YV	30W	220-240V	24V	0-1.25A	0.97	-30°C - 50°C	-40°C - 80°C	245x30x21mm
	LF-GMR045YV	45W	220-240V	24V	0-1.88A	0.95	-30°C - 50°C	-40°C - 80°C	245x30x21mm
	LF-GMR060YV	60W	220-240V	24V	0-2.50A	0.97	-30°C - 50°C	-40°C - 80°C	285x30x21mm
	<b>Free Flicker</b>	LF-GMR075YV	75W	220-240V	24V	0-3.13A	0.97	-30°C - 50°C	-40°C - 80°C